

OLYMPUS®

Your Vision, Our Future

**VISERA
ELITE II**

HD 3CMOS CAMERA HEAD

CH-S200-XZ-EB

Compact Size and Light Weight



3CMOS Sensor

- Broad covering of color gamut and enriched color reproducibility in full HD

Special Light Observation

- Select NBI and two modes of IR observation using only one remote button

Small, Compact Designs and Light Weight

- Offers an easy fit in the hand and maneuverability

2x Optical Focus Zoom

- Magnified observation without image quality deterioration

Fiber Mode

- Prevents the moiré effect caused by the combination of camera head and flexible or semirigid scope

Specifications

| | | | | | | |
|---|---|---|----|----|-----|----|
| Size | Camera head dimensions (unit: mm) | 97 | 44 | 38 | 113 | 49 |
| | Camera head weight | 220 g | | | | |
| Observation | Cable | ø 6.8 mm × 3 m | | | | |
| | Pickup system | CMOS image sensor × 3 | | | | |
| | Magnification ratio | Focal length f = 15.9 to 31.3 mm | | | | |
| NBI Observation Mode* | | Available | | | | |
| IR Telescopes Observation Mode* | | Available | | | | |
| Electronic Shutter Function* | | Available | | | | |
| Electronic Zoom Function* | | Available | | | | |
| | Cleaning/disinfection | Immersible in disinfectant solution | | | | |
| Cleaning/Disinfection/Sterilization | Sterilization | STERRAD 100S (Short cycle) 100NX (Duo cycle) NX (Standard cycle) V-PRO maX (Non Lumen cycle) | | | | |
| Classification (Electromedical Equipment) | Type of protection against electric shock | TYPE BF | | | | |
| | Degree of protection against explosion | The camera head should be kept away from flammable gases | | | | |

*For more details, refer to the instruction manual for the video system center.

Specifications, design and accessories are subject to change without any notice or obligation on the part of the manufacturer.



OLYMPUS MEDICAL SYSTEMS CORP.
Shinjuku Monolith, 2-3-1 Nishi-Shinjuku, Shinjuku-ku, Tokyo 163-0914, Japan

For a complete listing of sales and distribution locations visit
www.olympus.com